

SAMEDI 28.3 OPEN




FRAME Samedi 28 Open, 6061 T4-T6 alloy, variable thickness hydroformed tubes, Bosch PowerTube battery integration (Vertical), integrated cable routing	CASSETTE Shimano, Nexus, 30T	AUTONOMY 132km
SEATCLAMP Moustache, alloy, 34.9mm	CHAIN Shimano, HG40, 118 links	GVWR 135kg
HEADSET FSA, No 57B-1	REAR DERAILLEUR Shimano, Alfine, chain tensioner	WEIGHT 25.6kg
FORK SR Suntour, NEX-E25, 63mm travel	SHIFTER Shimano, Nexus SL-C7000-5, 5-speed	SIZES S (1,49 - 1,61m) M (1,59 - 1,76m) L (1,74 - 1,90m)
MOTOR Bosch, Active Line Plus, 250W, 35/50Nm	CRANKS Moustache, aluminium, 170mm	COLORS Titanium mat
BATTERY Bosch, PowerTube 500Wh, vertical	CHAINRING Narrow-Wide, 40 teeth	CONDITIONS Maximum distance, calculated for a 70kg rider in ideal conditions. Estimate your battery range .
DISPLAY Bosch, Purion - « Walk assist »	PEDALS alloy platform with reflectors	WARRANTY 5 years frame and fork Moustache Bikes - 2 years motor, battery
CHARGER Bosch, 4Ah	FRONT BRAKE Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake	
RIMS Moustache, asymmetric, alloy 6061E, welded, 32 holes, 28", internal width 23mm	FRONT ROTOR Shimano, 180mm or Alhonga, 180mm	
FRONT HUB Shimano, 32H, 9x100mm, QR (Quick Release)	REAR BRAKE Shimano, MT200 or Alhonga HJ-472, hydraulic disc brake	
TYRES Schwalbe, Big Apple, 700x50C	REAR ROTOR Shimano, 160mm or Alhonga, 160mm	
REAR HUB Shimano, Nexus, 32H, 10x135mm, nut	FRONT LIGHT AXA, Blueline, 30 lux, powered by main battery	
HANDLEBAR Moustache, ergonomic, alloy, 80mm rise	REAR LIGHT Spanninga, Presto2Guard, powered by main battery	
GRIPS Ergonomic, dual-density	MUDGUARD Moustache, alloy, double wall design, w/alloy stays	
SADDLE Selle Royal, Wave	CARRIER Moustache, alloy, removable QL3 lateral fixation, MIK HD platform	
SEATPOST Suspension, alloy, 31.6mm, 350mm, 40mm travel	KICKSTAND Moustache, adjustable	



Scan to find this bike online

{MOUSTACHE

SAMEDI 28.3 OPEN



TAILLE - ST	mm	390 (S)	450 (M)	510 (L)
Taille utilisateur (à titre indicatif)	m	1,49 - 1,61	1,59 - 1,76	1,74 - 1,90
Tube supérieur (mesure horizontale) - TT	mm	555	580	605
Bases - RC	mm	475	475	475
Douille de direction - HT	mm	170	170	170
Empattement - WB	mm	1101	1115	1124
Longueur de fourche - FL	mm	477	477	477
Hauteur boîtier - BB	mm	305	305	305
Angle de selle - SA	°	71,5	71,5	71,5
Angle de direction - HA	°	67,7	68,5	68,5
Reach	mm	342	366	390
Stack	mm	644	644	644



Scan to find this bike online

TOUSTACHE